




MULTIFIT TYPE

SAE STANDARD CONNECTIONS

M12810

NPTF MALE 60° CONE SEAT - SAE J516/J514



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm				
	DN	inch	Size		T	B	A	C	H ₁
M12810-03-02	5	3/16"	- 03	1/8" - 27	4,0	23,6	10,0		12
M12810-03-04	5	3/16"	- 03	1/4" - 18	5,5	29,1	14,5		14
M12810-04-02	6	1/4"	- 04	1/8" - 27	4,0	24,1	10,0		12
M12810-04-04	6	1/4"	- 04	1/4" - 18	5,5	29,0	14,5		14
M12810-04-06	6	1/4"	- 04	3/8" - 18	9,3	31,5	14,5		19
M12810-04-08	6	1/4"	- 04	1/2" - 14	9,3	33,5	19,2		24
M12810-05-04	8	5/16"	- 05	1/4" - 18	5,5	30,0	14,5		14
M12810-05-06	8	5/16"	- 05	3/8" - 18	9,3	32,0	14,5		19
M12810-06-04	10	3/8"	- 06	1/4" - 18	5,5	30,1	14,5		14
M12810-06-06	10	3/8"	- 06	3/8" - 18	9,3	28,6	14,5		19
M12810-06-08	10	3/8"	- 06	1/2" - 14	12,5	34,6	19,2		24
M12810-08-06	12	1/2"	- 08	3/8" - 18	9,3	28,9	14,5		19
M12810-08-08	12	1/2"	- 08	1/2" - 14	12,5	34,9	19,2		24
M12810-08-12	12	1/2"	- 08	3/4" - 14	16,0	35,4	19,2		27
M12810-10-08	16	5/8"	- 10	1/2" - 14	12,5	38,7	19,2		24
M12810-10-12	16	5/8"	- 10	3/4" - 14	16,0	40,2	19,2		27
M12810-12-12	19	3/4"	- 12	3/4" - 14	16,0	36,5	19,2		27
M12810-12-08	19	3/4"	- 12	1/2" - 14	12,5	36,5	13,6		27
M12810-12-16	19	3/4"	- 12	1" - 11,5	19,8	46,0	24,2		36
M12810-16-12	25	1"	- 16	3/4" - 14	15,5	38,8	19,2		32
M12810-16-16	25	1"	- 16	1" - 11,5	19,8	43,8	24,2		36
M12810-16-20	25	1"	- 16	1.1/4" - 11,5	26,0	56,3	25,0		46
M12810-20-20	31	1.1/4"	- 20	1.1/4" - 11,5	26,0	56,5	25,0		46
M12810-24-24	38	1.1/2"	- 24	1.1/2" - 11,5	32,0	57,6	26,0		50
M12810-32-32	51	2"	- 32	2" - 11,5	45,0	64,3	26,5		65
M12810-40-40	63	2.1/2"	- 40	2.1/2" - 8	55,4	78,0	39,9		80
M12810-48-48	76	3"	- 48	3" - 8	68,9	86,0	41,5		100