



M20812

BSP O-RING FEMALE 60° CONE - BS5200 / ISO 12151-6 (THRUST-WIRE NUT)



M20813

BSP O-RING FEMALE 60° CONE - BS5200 / ISO 12151-6 (SLIP-ON NUT)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm				
	DN	inch	Size		T	B	A	C	H ₂
M20813-03-04	5	3/16"	- 03	1/4" - 19	4,0	16,5	4,9		19
M20813-04-04	6	1/4"	- 04	1/4" - 19	4,0	17,5	4,9		19
M20812-06-04	10	3/8"	- 06	1/4" - 19	4,0	18,1	4,9		19
M20813-06-06	10	3/8"	- 06	3/8" - 19	7,0	20,4	6,1		22
M20813-06-08	10	3/8"	- 06	1/2" - 14	9,3	21,0	6,5		27
M20813-08-08	12	1/2"	- 08	1/2" - 14	9,3	20,4	6,5		27
M20812-10-10	16	5/8"	- 10	5/8" - 14	12,5	22,1	9,7		28
M20812-12-12	19	3/4"	- 12	3/4" - 14	15,0	25,0	8,5		32
M20812-16-12	25	1"	- 16	3/4" - 14	15,0	26,0	8,5		32
M20812-16-16	25	1"	- 16	1" - 11	19,8	27,3	10,6		38
M20812-16-20	25	1"	- 16	1.1/4" - 11	26,1	30,8	10,5		50
M20812-20-16	31	1.1/4"	- 20	1" - 11	19,8	29,0	10,5		38
M20812-20-20	31	1.1/4"	- 20	1.1/4" - 11	26,0	31,5	10,5		50
M20812-20-24	31	1.1/4"	- 20	1.1/2" - 11	32,1	29,5	12,5		60
M20812-24-20	38	1.1/2"	- 24	1.1/4" - 11	26,0	31,5	10,5		50
M20812-24-24	38	1.1/2"	- 24	1.1/2" - 11	32,0	30,5	12,5		60
M20812-24-32	38	1.1/2"	- 24	2" - 11	42,0	30,0	16,1		70
M20812-32-32	51	2"	- 32	2" - 11	42,0	31,9	16,1		70