




# INTERLOCK PLUS TYPE



## BS STANDARD CONNECTIONS

### M30510


BSP MALE PARALLEL 60° CONE SEAT - BS5200 / ISO 8434-6



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm				
	DN	inch	Size		T	B	A	C	H <sub>1</sub>
M30510-12-12	19	3/4"	- 12	3/4" - 14	17,0	36,9	16,0	32	
M30510-12-16	19	3/4"	- 12	1" - 11	22,5	43,0	19,0	41	
M30510-16-16	25	1"	- 16	1" - 11	22,5	42,8	19,0	41	
M30510-16-20	25	1"	- 16	1.1/4" - 11	29,0	47,5	20,0	50	
M30510-20-20	31	1.1/4"	- 20	1.1/4" - 11	28,5	50,5	20,0	50	
M30510-24-24	38	1.1/2"	- 24	1.1/2" - 11	33,5	54,4	22,0	55	
M30510-32-32	51	2"	- 32	2" - 11	42,0	57,8	25,0	70	

### M40812

BSP O-RING FEMALE 60° CONE - BS5200 / ISO 12151-6 (THRUST-WIRE NUT)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm				
	DN	inch	Size		T	B	A	C	H <sub>1</sub>
M40812-12-12	19	3/4"	- 12	3/4" - 14	14,5	38,8	8,5	32	32
M40812-12-16	19	3/4"	- 12	1" - 11	19,0	40,0	10,6	32	41
M40812-16-12	25	1"	- 16	3/4" - 14	15,0	40,0	8,5	38	32
M40812-16-16	25	1"	- 16	1" - 11	19,5	44,4	10,6	41	41
M40812-16-20	25	1"	- 16	1.1/4" - 11	26,0	43,5	10,1	41	50
M40812-20-16	31	1.1/4"	- 20	1" - 11	19,0	50,0	10,6	50	41
M40812-20-20	31	1.1/4"	- 20	1.1/4" - 11	25,0	52,4	10,1	50	50
M40812-20-24	31	1.1/4"	- 20	1.1/2" - 11	32,0	51,5	12,5	50	60
M40812-24-20	38	1.1/2"	- 24	1.1/4" - 11	26,0	52,5	10,1	60	50
M40812-24-24	38	1.1/2"	- 24	1.1/2" - 11	32,0	51,3	12,5	60	60
M40812-32-32	51	2"	- 32	2" - 11	42,0	51,6	16,1	70	70