



### M40892



90° BSP O-RING FEMALE SWEPT ELBOW 60° CONE BS5200 / ISO 12151-6 (THRUST-WIRE NUT)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C	E	H <sub>2</sub>
M40892-12-12	19	3/4"	- 12	3/4" - 14	14,5	72,4	8,5	70,0		32
M40892-12-16	19	3/4"	- 12	1" - 11	19,0	72,0	10,6	71,0		41
M40892-16-16	25	1"	- 16	1" - 11	19,5	82,2	10,6	80,5		41
M40892-16-20	31	1.1/4"	- 20	1.1/4" - 11	25,0	95,0	10,1	78,5		50
M40892-20-20	31	1.1/4"	- 20	1.1/4" - 11	25,0	98,5	10,1	98,0		50
M40892-24-24	38	1.1/2"	- 24	1.1/2" - 11	32,0	111,5	12,5	109,0		60
M40892-32-32	51	2"	- 32	2" - 11	42,0	143,2	16,1	140,5		70

### M40842



45° BSP O-RING FEMALE SWEPT ELBOW 60° CONE BS5200 / ISO 12151-6 (THRUST-WIRE NUT)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C	E	H <sub>2</sub>
M40842-12-12	19	3/4"	- 12	3/4" - 14	14,5	88,0	8,5	35,0		32
M40842-12-16	19	3/4"	- 12	1" - 11	19,0	89,5	10,6	36,5		41
M40842-16-12	25	1"	- 16	3/4" - 14	15,0	105,5	8,5	36,0		32
M40842-16-16	25	1"	- 16	1" - 11	19,5	97,0	10,6	40,0		41
M40842-16-20	25	1"	- 16	1.1/4" - 11	26,0	108,5	10,1	38,0		50
M40842-20-16	31	1.1/4"	- 20	1" - 11	19,0	118,0	10,6	47,5		41
M40842-20-20	31	1.1/4"	- 20	1.1/4" - 11	25,0	120,0	10,1	49,5		50
M40842-20-24	31	1.1/4"	- 20	1.1/2" - 11	32,0	114,5	12,5	40,0		60
M40842-24-24	38	1.1/2"	- 24	1.1/2" - 11	32,0	126,5	12,5	50,0		60
M40842-32-32	51	2"	- 32	2" - 11	42,0	162,6	16,1	66,5		70