










GOLDENBLAST™

SAFE WATERBLAST TECHNOLOGY



								
PART REF.	HOSE SIZE	O.D.	MAX. W.P.	BURST PRESSURE	MIN. BEND RADIUS	WEIGHT	MF3000 FITTING	MF2000 FITTING

	DN	dash	inch	mm	inch	bar	psi	bar	psi	mm	inch	g/m	lbs/100 ft		
GB-06	10	-6	3/8"	20.2	0.80	750	10870	1875	27180	180	7.09	700	47	–	BL+M01700-06
GB-08	12	-8	1/2"	23.0	0.91	750	10870	1875	27180	220	8.66	825	55	–	BL+M01700-08

KEY PERFORMANCE

Basic hose line for scale removing applications • Compactness, lightness and flexibility • Safety factor 2,5:1 (accepted world standard as specified by RMA-USA, BFPA-UK, DIN-Germany, ISO 7751) • High abrasion resistance cover

MAIN APPLICATIONS

Scale removing applications using extreme high working pressure such as:

- building and industrial sectors (roadworks, removal of concrete from reinforced concrete structures safeguarding metal components)
- scale removal from ship's hull in shipyard
- dust elimination

CONTINUOUS SERVICE TEMPERATURE RANGE

+15°F / +158°F -10°C / +70°C

MAX. OPERATING TEMPERATURE

(intermittent service) 200°F / 93°C

RECOMMENDED FLUIDS

Water, water soap, emulsions

INSERT: MF2000® - BLASTLOCK TYPE

TUBE: Water resistant synthetic rubber

REINFORCEMENT: Four high tensile steel spirals

COVER: Synthetic rubber with high temperature ozone, and abrasion resistance

APPLICABLE SPECS.: MANULI® Design, Australian Std. AS/NZS 4233.2

TYPE APPROVALS: GOST-R