









# PUSH-ON HOSE

300 PSI



												
PART REF.	HOSE SIZE		O.D.		MAX. W.P.		MIN. BEND RADIUS		WEIGHT		FITTINGS (PUSH-ON)	

	DN	dash	inch	mm	inch	bar	psi	mm	inch	g/m	lbs/ft	
H9203-4-R	6	-4	1/4"	14	0.54	20.69	300	60	2.36	104.2	0.07	BRASS PUSH-ON HOSE BARB
H9203-5-R	8	-5	5/16"	16	0.61	20.69	300	76	3.00	133.9	0.09	BRASS PUSH-ON HOSE BARB
H9203-6-R	10	-6	3/8"	17	0.69	20.69	300	76	3.00	208.3	0.14	BRASS PUSH-ON HOSE BARB
H9203-8-R	12	-8	1/2"	21	0.81	20.69	300	127	5.00	238.1	0.16	BRASS PUSH-ON HOSE BARB
H9203-10-R	16	-10	5/8"	24	0.93	20.69	300	152	6.00	312.5	0.21	BRASS PUSH-ON HOSE BARB
H9203-12-R	19	-12	3/4"	34	1.34	20.69	300	203	8.00	506.0	0.34	BRASS PUSH-ON HOSE BARB

## MAIN APPLICATIONS

For use with push-on fittings at maximum working pressures of 300 psi. For low pressure hydraulic, pneumatic systems such as robotics, shop air systems, general industrial, maintenance and automotive applications

## CONTINUOUS SERVICE TEMPERATURE RANGE

-40°F / +190°F -40°C / +88°C

**TUBE:** Seamless, black, oil and heat resistant synthetic rubber

**REINFORCEMENT:** Braided (1) high strength synthetic yarn laid at an angle for strength and coupling holding ability

**COVER:** Black, oil, abrasion and weather resistant synthetic rubber, smooth finish

**STANDARD PACKAGING.:** Reel