

SPIRTEX/K

SAE 100 R4



PART REF.	HOSE SIZE	O.D.	MAX. W.P.	BURST PRESSURE	MIN. BEND RADIUS	WEIGHT	MF3000 FITTING	MF2000 FITTING

	DN	dash	inch	mm	inch	bar	psi	bar	psi	mm	inch	g/m	lbs/100 ft		
SPK-10	16	-10	5/8"	26.0	1.02	21	300	64	930	96	3.78	590	40	-	MF+M00310-10
SPK-12	19	-12	3/4"	29.0	1.14	21	300	84	1220	125	4.92	550	37	OPS	MF+M00310-12
SPK-16	25	-16	1"	35.0	1.38	17	250	70	1010	150	5.91	680	46	OPS	MF+M00920-16
SPK-20	31	-20	1-1/4"	42.0	1.65	14	200	56	810	200	7.87	840	56	OPS	MF+M00920-20
SPK-24	38	-24	1-1/2"	48.5	1.91	10	140	42	610	254	10.00	1024	70	OPS	MF+M00910-24
SPK-32	51	-32	2"	61.5	2.42	7	100	28	410	300	11.81	1420	95	OPS	MF+M00910-32
SPK-40	63	-40	2-1/2"	76.0	2.99	4	62	17	250	355	13.98	2150	144	-	MF+M03400-40
SPK-48	76	-48	3"	88.0	3.46	4	56	16	230	457	17.99	2850	191	-	MF+M03400-48
SPK-56	89	-56	3-1/2"	103.0	4.06	3	45	12	180	530	20.87	3450	231	-	*
SPK-64	102	-64	4"	115.0	4.53	2	35	10	140	610	24.02	3900	261	-	*

* The complete code for each item is composed by 13 digits, the last 4 digits indicate the type of packaging. Please see the full list of alternative options on Manuli website.

* Contact Manuli Rubber Industries.

KEY PERFORMANCE

Resistance to vacuum • New compact SAE 100 R4 architecture

MAIN APPLICATIONS

Suction lines, return lines

CONTINUOUS SERVICE TEMPERATURE RANGE

-40°F / +212°F -40°C / +100°C

RECOMMENDED FLUIDS

Mineral oils, vegetable and rape seed oils, glycol and polyglycol-based oils, synthetic ester-based oils, oils in aqueous emulsion, water

TUBE: Oil resistant synthetic rubber

REINFORCEMENT: Two textile reinforcements with steel helical body wire

COVER: Environment resistant synthetic rubber

APPLICABLE SPECS.: SAE 100 R4

TYPE APPROVALS: GOST-R

STANDARD PACKAGING: Reel

